

# Unitary Heat Pump Water Heater



For Existing Single Family or Existing Manufactured Homes

[www.fallriverelectric.com](http://www.fallriverelectric.com)

Member Number		Phone #	
Member Name		Mobile #	
Mailing Address	City	State	Zip
Installation Address (if different than above)	City	State	Zip
Email			
Home type: <input type="checkbox"/> Existing Site Built <input type="checkbox"/> Existing Manufactured			

\*Only Heat Pump Water Heaters replacing electric tanks are eligible.

## NEW EQUIPMENT INFORMATION

Brand Installed	Model	Size(gallons)	Installed Date
Installation Location: <input type="checkbox"/> Heated Location <input type="checkbox"/> Unheated Location			

\*Unitary Heat Pump Water Heater (HPWH) combine the tank and compressor in a single unit.

**Please provide Fall River Electric with a copy of the installed unitary heat pump water heater invoice, showing manufacturer and model number.**

Measure description	Member Rebate	
Unitary HPWH All Tiers - 40 gallon tank <small>not available for new construction</small>	\$500.00	<b>Contact Fall River Electric for Qualified Product list.</b>  <b>Requirements and specifications listed on back.</b>
Unitary HPWH Tier 3-Over 50 gallons	\$550.00	
Unitary HPWH Tier 4-Over 50 gallons	\$650.00	
Split-System Heat Pump Water Heater-Any Size tank	\$750.00	

**A maximum of one Unitary Heat Pump Water Heater measure may be claimed per home.**

Purchases must be made after 4/1/2023 and installed in FRE service territory to be eligible. All incentives are subject to availability and may change at any time. FRE reserves the right to inspect for program compliance. By signing, the Member certifies that the above information is true and accurate to the best of their knowledge.

Member Signature \_\_\_\_\_

Date \_\_\_\_\_

Office Use Only		
GL: <u>CONS 14 300 555.13</u>	FRE Representative _____	Pay \$ _____
Effective 4/1/2023	PROMOTIONAL REBATE	Date: _____

**Requirements:**

- Must be installed according to manufacturer's specifications.

**Split-System Requirements:**

- All water or refrigerant lines connecting the tank and outdoor units shall be insulated with minimum R-4.
- If domestic hot water pipes outdoors are freeze-protected with heat cable, the cable shall be installed per manufacturer's instructions, underneath the insulation, and shall be thermostatically controlled to prevent the tape from operating above 38 degrees Fahrenheit.
- No resistance heating is allowed (except heat tape for freeze protection).
- System plumbed with a thermal mixing valve, which is equipped with internal check valves on the hot and cold water lines connecting to it.
- A maximum of one Split-System HPWH measure may be claimed per building. Accessory dwelling units with separate plumbing systems or separate HVAC systems qualify for applicable measures even if they are on the same electrical meter.